



Tire Balancing Beads

- Increases tire life and improves fuel economy
- Reduces vibration
- Tires are balanced all the time, not just over 30 mph
- No rebalancing every time you come to a stop
- No dust to clog valves
- Free valve cap & new valve stem with every bag
- Guaranteed to work with Internal Tire Pressure Monitors

Service Department Packs



- Includes the balancing beads, valve stems and caps for 4 applications.
- To install, simply toss in a bag when mounting a tubeless tire.

PTI PART #	ITEM DESCRIPTION	RETAIL
33-1001	Set of 4 - 1 oz. bags	12.95 per tire
33-1002	Set of 4 - 2 oz. bags	14.95 per tire
33-1003	Set of 4 - 3 oz. bags	17.95 per tire

Retail Do It Yourself Kits



- Includes balancing beads, applicator bottle with tube, valve core remover, valve stems and caps.
- Use this for "on the bike" applications and any tube type installation.

PTI #	ITEM DESCRIPTION	RETAIL
33-1011	Motorcycle Kit B, 1 - 1 oz. & 1 - 2 oz. bags	27.95 per kit
33-1013	Motorcycle Kit D, 2 - 2 oz. bags	29.95 per kit
33-1016	Motorcycle Kit E, 1 - 2 oz. & 1 - 3oz. bags	32.95 per kit
33-1018	Trike Kit F, 1 - 2oz. & 2 - 3oz. bags	41.95 per kit

Application Guide

WHEEL POSITION	TIRE WIDTH	AMOUNT PER TIRE
Motorcycle - Street		
Front	80-120 mm	1 oz*
Front	80-120 mm (BMW Telelever only)	2 oz
Front	130 and up	2 oz
Rear	130 - 240 mm	2 oz
Rear	250 - 360 mm	3 oz
Rear	195 - 205 mm Car Tires	3 oz
Motorcycle - Dual sport / off road w/o rim locks		
Front	80-120 mm	1 oz
Rear	130 - 230 mm	2 oz
Motorcycle - Dual sport / off road with rim locks		
Front	80-120 mm	2 oz
Rear	130 - 230 mm	3 oz
Scooter		
Any	Up to 10" Diameter	1oz
Any	12" & Up Diameter	2 oz

EXCEPTIONS

- Front tires on sport bikes at triple digit speeds can experience vibration because too much weight was added. Please start with a ¼ ounce.
- Thin front tires with tubes and spoke rims that the chart calls for 1 oz. please add 2 oz.



800-523-2542